


GaN & GaAs Products & Foundry solutions



Sub-7GHz • Mid band & mmw RAN • 5G NTN • FWA 26, 28, 39, 47GHz • 5G Test & Measurement • Repeater & Indoor • V, E, W & D band Radio Backhaul

Innovative design


- Linearizability of GaN HPA demonstrated with 256QAM-OFDM Signal & Digital PreDistortion
- 39GHz Front-End OFDM 5G compliant for MIMO Antenna
 - Linear High Power Amplifier
 - Very Low Noise Amplifier
 - Fast & high isolation Switch
- System in Package (SiP)
 - Multichip Integration SiGe/GaAs /GaN
- FO-WLP demonstrator



@ CEA-Leti

New MMICs

- LNAs 30-44GHz
- 1.8dB NF & 2.5V/28mA bias
- HPAs 24-28 & 27-31.5GHz
- 14W in QFN package



EVB CHA8682-QWA in QFN 6x5

*Best in class SWaP-C :
Size Weight & Power-Cost*

- Front-End 26/28/39GHz CHC6054/6094 OFDM 5G SWaP-C for MIMO
- GaN/SiC power bar 4-140W
- Linear MPA & HPA up to 43.5GHz
- V & E-Band MPA, LNA, Mixer chipset
- W-Band LNA
- Compact combiner/divider 2/3 way 8 to 35GHz

Released Technologies

GaN / SiC RF Power & PAE

- GH25 < 20GHz
- GH15 < 45GHz
- New GH10 < 90GHz

GaAs Linear & Low Noise

- PPH25/15x linearity <45GHz
- PH10 Low Noise < 100GHz
- PH15 Low Noise < 80GHz
- PH25 Low Noise < 60GHz
- BES Schottky diode < 3THz
- ULRC Power Passive

Plastic Package

- QFN available 3x3 to 8x8mm²
- DFN 2x2mm² to 3x4mm²
- MSL 1, 2, 3



Building blocks for your



projects

SUB-7GHz (FR1)

NEW

MPA	Freq (GHz)	Gain (dB)	IP3 (dBm)	OPI dB (dBm)
CHA5005-QDG	0.9-1.8	18.5	-	26.5
CHA4105-QDG	2-4	23	-	24
GaN transistors	Freq (GHz)	small signal Gain (dB) @ freq (GHz)	Power(W)	PAE % @ Freq (GHz)
CHKA012-99F	Up to 4	19@3	140	65@3
CHK015AaQIA	Up to 4	18@3	20	55@3
CHK8101a99F	Up to 6	14@6	20	60@6
CHK9013-99F	Up to 8	18@6	88	65@6
CHK5010-99F	Up to 12	22@6	4	72@6
CHK9014-99F	Up to 13	13@12	60	50@12
HPA	Freq (GHz)	Gain (dB)	IP3 (dBm)	Psat (dBm)
CHA8107-QCB	4.5-6.8	28	-	41

6-24GHz (FR3)

LNA	Freq (GHz)	Gain (dB)	Nf (dB)	OPI dB (dBm)
CHA3656-QAG	6-17	20	1.7	14
CHA2110-QDG	7-12	19	1.2	10
CHA1252-QDG	11-18	22	1.3	7
GaN HPA	Freq (GHz)	Gain (dB)	Psat (dBm)	OIP3 (dBm)
CHA7060-QAB	5.6-8.5	30	41	45
CHA7250-QAB	10-12.75	20	40	45
CHA7063-QCB	12.7-20	20	ACPR:33dBc@30dBm P _{out} 200MHz/256QAM	
MPA /VGA	Freq (GHz)	Gain (dB)	IP3 (dBm)	OPI dB (dBm)
CHA4220-QGG	0.5-20	17	28	20
CHA3024-QGG	2-22	15	28	18
CHA4350-QDG	5.5-11.7	26	32	24
Linear Attenuator	Freq (GHz)	Ins. Loss (dB)	P-1dB In	Amplitude Control (dB)
CHT4690-QAG	5-30	4	25	31
Wilkinson	Freq (GHz)	Loss (dB)	Isolation (dB)	Return Loss (dB)
CHW4212-QKA	8-22	0.5	20	>20
Power Detector	Freq (GHz)	Loss (dB)	Dyn. Range(dB)	Type
CHE1270-QAG	5-44	-	30	Wide-Band

24-30GHz (FR2)

RF Front End	Freq (GHz)	Gain RX/ Gain TX (dB)	Pout RX/ Pout Tx (dBm)	NF RX
CHC6054-QQA	24.25-30.5	18/28	10/31	3.2
HPA	Freq (GHz)	Gain (dB)	IP3 (dBm)	Psat (dBm)
CHA6652-QXG	21-27.5	20	41	33
CHA8682-QWA	24.5-28	30	-	42.5
CHA8267-QWA	27-31.5	25	-	42.5
CHA8265-98F	27.5-31	25	-	44
CHA6653-QXG	27-33.5	20	38	33
CHA6357-QKB	27.5 - 30	27	ACPR-35dBc	35
CHA7362-QWA	27.5-31	26	ACPR-30dBc	39
MPA	Freq (GHz)	Gain (dB)	IP3 (dBm)	OPI dB (dBm)
CHA3395-QDG	21-30	24	32	20
CHA4396-QDG	24-30	22	31	21
LNA	Freq (GHz)	Gain (dB)	NF (dB)	OPI dB (dBm)
CHA3688aQDG	12.5-30	26	2	14
CHA1351-QAG	24-32	22	1.3	5
CHA2595-QDG	27.5-43.5	19.5	2.3	11
Down-Converter	Freq (GHz)	Conv. Gain (dB)	NF (dB)	IPI dB (dBm)
CHR2295-99F	24-30	11	3.5	-10
Wilkinson	Freq (GHz)	Ins. Loss (dB)	Isol. Range (dB)	Return Loss (dB)
CHW4312-QKA	22-34	0.75	20	>15
CHW4313-QAG	24-35	0.6	20	>16

37-52.6GHz (FR2)

LNA	Freq (GHz)	Gain (dB)	NF (dB)	OPI dB (dBm)
CHA1452-QDG	30-44	24	1.8	4
CHA2452-QAG	31-43	20	1.8	8
CHA2352-98F	46-52	21	3.5	12
MPA	Freq (GHz)	Gain (dB)	IP3 (dBm)	P-1dB (dBm)
CHA3397-QDG	36-40.5	21	29	18
CHA3398-QDG	36-43.5	22	29	18
HPA	Freq (GHz)	Gain (dB)	IP3 (dBm)	Psat (dBm)
CHA6094-QKB	35-42.5	26	ACPR:29dBc@29dBm P _{out} 120MHz/256QAM	
CHA6095-QKB	35-42.5	25	ACPR:30dBc@31dBm P _{out} 120MHz/256QAM	
CHA5659-QXG	36-43.5	20	38.5	30
CHA6194-QXG	37-40	20	38	31
CHA8454-99F	37.6-43.5	24	-	40.5
RF Front End	Freq (GHz)	Gain RX/ Gain TX (dB)	Pout RX/ Pout Tx (dBm)	NF RX
CHC6094-QKB	37-41	29/23	11/33	4.8

V-BAND

LNA	Freq (GHz)	Gain (dB)	NF (dB)	OPI dB (dBm)
CHA2159-99F	55-65	20	4	14
CHA2368-98F	50-71	20	3.5	11

Mixer	Freq (GHz)	Freq LO (GHz)	Conv gain (dB)	IPI dB (dBm)
CHM1294-99F	35-45	16-24	-11	0
CHM1298-99F	55-65	27.5-32.5	-12	0

E-BAND

LNA/VGA	Freq (GHz)	Gain (dB)	NF (dB)	OPI dB (dBm)
CHA2080-98F	71-86	22	3.5	10
MPA/VGA	Freq (GHz)	Gain (dB)	IP3 (dBm)	OPI dB (dBm)
CHA3080-98F	71-76	16	25	19
CHA3090-98F	81-86	13	23	17
Mixer	Freq (GHz)	Freq LO (GHz)	Conv gain (dB)	IPI dB (dBm)
CHM1080-98F	71-86	34.5-44	-11	10
CHR1080a98F	71-86	34.5-44	8	-10

W-BAND

LNA	Freq (GHz)	Gain (dB)	NF (dB)	OPI dB (dBm)
CHA1008-99F	80-105	17	6.5	5

Ka-BAND HPAs for 5G NTN High Capacity Uplinks

CHA8682-98F

- 25-29GHz
- 25W
- 28% PAE
- 3.6x3.6mm²

CHA8265-98F

- 27.5-31GHz
- 25W
- 30% PAE
- 3.6x3.6mm²

- > Smallest Form Factor
- > GaN/SiC Low Thermal resistance
- > Wideband linear with complex waveform

