

7-11GHz Low Noise Amplifier


GaAs Monolithic Microwave IC

Description

The CHA1010-99F is a monolithic three-stage wide-band low noise amplifier.


It is designed for a wide range of applications, from military to commercial communication systems.

The circuit is manufactured with a pHEMT process, via holes through the substrate, air bridges and electron beam gate lithography. It is available in chip form.



Main Features

- Broadband performance: 7-11GHz
- 1dB Noise Figure
- 32dB Linear Gain
- +5.5dBm Pout at 1dB gain compression
- DC bias: Vd=5Volt, Id=30mA
- Chip size 2.57x1.79x0.1mm



Main Electrical Characteristics

Tamb= +25°C. Vd = +5.0V

Symbol	Parameter	Min	Typ	Max	Unit
Freq	Frequency range	7		11	GHz
Gain	Linear Gain		32		dB
NF	Noise Figure		1.0		dB
Pout	Output Power @1dB compression		5.5		dBm

Electrical Characteristics

Tamb= +25°C. Vd = +5.0V

Symbol	Parameter	Min	Typ	Max	Unit
Freq	Frequency range	7.0		11.0	GHz
Gain	Linear Gain		32		dB
ΔG	Gain Flatness		1.1		dBpp
-	Linear Gain Variation over Temperature		0.06		dB/°C
NF	Noise Figure		1.0		dB
S11	Input Return Loss		-15		dB
S22	Output Return Loss		-15		dB
OP1dB	Output power at 1dB gain compression		5.5		dBm
IP1dB	Input power at 1dB gain compression		-24.5		dBm
Id	Drain Bias Current		30		mA
Vg	Gate Bias Voltage		-0.5		V
Rth_eq ⁽¹⁾	Chip's equivalent thermal resistance at +85°C		73		°C/W

These values are representative of on-test-fixture measurements that are made with bonding wires of typically 0.5nH at both RF accesses.

⁽¹⁾ Under linear regime

Absolute Maximum Ratings ⁽¹⁾T_{amb}= +25°C

Symbol	Parameter	Values	Unit
V _d	Drain bias voltage	6.5V	V
I _d	Drain bias current	120	mA
V _g	Gate bias voltage	-1.5 to +0.4	V
T _a	Operating temperature range	-40 to +85	°C
T _j	Operating temperature range	175	°C
T _{stg}	Storage temperature range	-55 to +150	°C
P _{in}	Maximum peak input power overdrive	-19	dBm

⁽¹⁾ Operation of this device above anyone of these parameters may cause permanent damage**Typical Bias Conditions**T_{amb}= +25°C

Symbol	Pad N°	Parameter	Values	Unit
V _d	5	Drain Supply Voltage	5	V
V _g	2	Gate Supply Voltage	-0.5	V

Typical on-wafer Sij parameters




Tamb.= +25°C. Vd = +5.0V. Id = 30mA

Freq (GHz)	S11 (dB)	PhS11 (°)	S12 (dB)	PhS12 (°)	S21 (dB)	PhS21 (°)	S22 (dB)	PhS22 (°)
5.1	-10.80	-58.03	-61.90	54.37	24.94	-48.37	-0.85	-84.29
5.3	-10.27	-62.00	-72.70	-54.03	26.61	-68.12	-1.14	-89.70
5.5	-9.92	-67.59	-63.66	-4.19	27.86	-89.08	-1.54	-95.11
5.7	-9.92	-72.93	-61.58	18.47	28.84	-108.21	-2.04	-100.62
5.9	-9.66	-78.21	-65.24	12.09	29.63	-127.13	-2.79	-106.09
6.1	-9.85	-83.47	-65.51	39.48	30.27	-146.21	-3.62	-111.60
6.3	-10.13	-87.45	-59.20	-31.56	30.74	-165.09	-4.63	-116.21
6.5	-10.16	-90.49	-58.73	-35.20	31.05	177.63	-5.85	-119.81
6.7	-10.34	-93.78	-55.59	-13.19	31.21	160.10	-7.33	-121.26
6.9	-10.20	-97.39	-67.30	-50.15	31.43	143.99	-9.09	-119.57
7.1	-10.26	-101.77	-59.68	-65.41	31.36	128.38	-10.70	-114.95
7.3	-10.31	-105.80	-63.66	-31.66	31.33	113.37	-11.65	-105.90
7.5	-10.67	-109.76	-51.48	-88.44	31.30	99.60	-12.00	-96.04
7.7	-11.10	-113.74	-55.72	-86.69	31.09	85.75	-11.31	-88.97
7.9	-11.45	-117.43	-50.32	-103.79	31.05	73.30	-10.80	-84.16
8.1	-12.39	-121.38	-57.82	-122.16	30.90	60.95	-10.24	-83.85
8.3	-12.93	-125.60	-52.25	-141.54	30.83	49.35	-10.00	-83.94
8.5	-14.12	-127.28	-54.97	-136.25	30.75	38.01	-9.82	-85.55
8.7	-15.21	-127.93	-60.31	129.45	30.72	26.83	-9.76	-86.61
8.9	-16.29	-122.59	-50.91	-162.43	30.73	15.95	-9.60	-87.82
9.1	-17.91	-114.34	-53.37	-150.22	30.75	4.99	-9.64	-88.31
9.3	-18.81	-103.08	-48.96	-179.11	30.78	-5.88	-10.08	-87.75
9.5	-18.81	-85.05	-50.20	173.25	30.89	-16.93	-10.32	-86.63
9.7	-17.16	-69.65	-49.64	159.17	31.02	-28.25	-10.63	-83.94
9.9	-15.03	-62.94	-48.28	167.83	31.08	-39.79	-10.65	-80.45
10.1	-12.71	-58.78	-48.71	149.39	31.06	-51.58	-10.40	-76.19
10.3	-10.88	-58.57	-46.41	147.72	31.03	-63.64	-9.77	-71.78
10.5	-9.10	-63.80	-47.99	138.17	31.01	-75.79	-8.84	-68.03
10.7	-7.75	-69.54	-46.49	111.34	30.80	-88.79	-7.82	-68.69
10.9	-6.71	-75.16	-46.79	112.74	30.71	-101.44	-6.61	-70.32
11.1	-5.87	-81.57	-44.51	97.71	30.38	-113.83	-5.56	-74.27
11.3	-5.17	-88.93	-46.65	89.09	29.98	-126.08	-4.75	-79.34
11.5	-4.72	-95.15	-45.18	67.63	29.53	-138.05	-4.02	-85.08
11.7	-4.30	-101.65	-45.33	77.90	28.96	-149.65	-3.47	-90.47
11.9	-4.13	-107.78	-49.59	61.27	28.36	-160.85	-3.15	-96.41
12.1	-4.01	-113.39	-47.68	41.15	27.72	-171.46	-2.94	-103.14
12.3	-3.91	-118.52	-47.05	28.46	27.11	178.57	-2.68	-109.32
12.5	-3.87	-123.53	-47.04	24.79	26.44	168.70	-2.50	-115.44
12.7	-3.90	-127.82	-48.55	17.93	25.72	159.59	-2.48	-120.71

Typical Wide-Band Test Fixture Measurements

Temperature= -40°C, +25°C, +85°C



Vd = +5.0V, Id = 30mA, Vg ~ -0.5V




Typical Test Fixture Measurements

Temperature= -40°C, +25°C, +85°C

Vd = +5.0V, Id =30mA, Vg ~ -0.5V



Mechanical data




Units: μm
 Tol: $\pm 35 \mu\text{m}$
 Chip thickness: $100\mu\text{m}$.
 Chip size: $2570 \times 1790 \pm 35\mu\text{m}$
 All dimensions are in micrometers

RF pad (1,7) size= $100 \times 200\mu\text{m}^2$

DC pad (2,3,4,5,6) size= $100 \times 100\mu\text{m}^2$

Pad number	Pad name	Description
1	IN	Input RF
2	VG	Gate Supply Voltage
3	GND	NC
4, 6	none	NC
5	VD	Drain Supply Voltage
7	OUT	Output RF

Recommended assembly plan



Note: 25µm-diameter gold wire and 25µm-wedge bonding are preferred.

Recommended circuit bonding table

Label	Type	Decoupling	Comment
VD	Vd	100pF & 10nF	Drain Supply
VG	Vg	100pF & 10nF	Gate Supply
IN	Input RF	N/A	Inductance~0.5nH (one golden bonding wire with 650µm length and 25µm diameter)
OUT	Output RF	N/A	Inductance~0.5nH (one golden bonding wire with 650µm length and 25µm diameter)

Notes

Recommended ESD management

Refer to the application note AN0020 available at <https://www.ums-rf.com> for ESD sensitivity and handling recommendations for the UMS products.

Recommended environmental management

UMS products are compliant with the regulation in particular with the directives RoHS N°2011/65 and REACH N°1907/2006. More environmental data are available in the application note AN0019 also available at <https://www.ums-rf.com>.

Ordering Information

Chip form: CHA1010-99F/00

Information furnished is believed to be accurate and reliable. However **United Monolithic Semiconductors S.A.S.** assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of **United Monolithic Semiconductors S.A.S.**. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. **United Monolithic Semiconductors S.A.S.** products are not authorised for use as critical components in life support devices or systems without express written approval from **United Monolithic Semiconductors S.A.S.**